### Useful Reference Points • www.hae.org.uk/businessguard

Betore Starting Work.

### **AAHA XHOW**

- ignite fumes from petrol or gas there is a danger of explosion. It will Do not use this brush cutter where
- never run the brush cutter indoors or injury from breathing toxic tumes, To reduce the risk of serious or fatal .S cylinders.
- Make sure that the area is clear and 31 in poorly ventilated locations.
- or could distract you. sate and that no-one is near to you
- and form injury. Keep people at least Protect other people form the noise ·t
- ·'G 10 metres (32 feet) away.
- other debris that could foul your stones, wire, stout branches and Before starting, clear the area of

### sepera buind

- minimum that should be worn protective equipment (ppe) are the 1. The following items of personal **SROTAR340**
- You must wear a faceshield (EN166 -.S require a higher level of protection. Particular jobs or environments may whenever you use this brush cutter.
- other debris from where you are brush cutter may throw up stones or working with this machine. The B or BS2092 grade 1) when you are
- noise levels up to 102 dB(A) wear .guixrow
- hearing protection for this level as a appropriate ear muffs or plugs giving

- 3. This equipment is likely to cause

- ามทนแบเน

มกอา รมมอติอม กระว

Association Europe

### is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability perc nave arisen from the use of any such document/material. Only Acts of Parliament and Statutory Ins to have arisen from the use of any such document/material. Only Acts of Parliament and Statu have the force of law and only the courts can authoritatively interpret the law. **3YT TEB Iludilos** The Crescent Birmingham Business Park

**'**G

·+

31

.S

-7

.9

**. G** 

\*\*

Every effort has been made by HAE/EHA to ensure that the information given in this document and supporting materia



w.hae.org.ul ail@hae.org.uk

Only use sharp blades.

or near ground level.

**BRUSH CUTTER** 

or BS1870/4972).

.sepsia

machine.

without using the harness.

contact the hire company.

company for the material being cut.

of blades recommended by the hire

Make sure you use the correct type

covered during storage or transport,

The cutting blades should be

Brushcutters should only be used at

Do not operate this brush cutter

Do not use anything found damaged

equipment including the harness.

will also need to wear appropriate

Anybody who is working near to you

when changing or adjusting the

You should wear gloves especially

You must wear safety boots (EN345

prevent it getting caught up in the

machine. Tie up any long hair to

(BS5240) when working with this

You must wear a safety helmet

1. Check your machine, engine and all

personal protective equipment.

to protect the blades and you.

**44** (0) 121 333 4109

## The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment. It is important to read all of this leaflet

### **BEFORE using the Brush Cutter**

1643 Safety Guidance

4 STROKE PETROL

- 1. Plan your work and think ahead to make sure you will
- always be working safely. Petrol is highly flammable. Take care not to cause a fire 2.
- or explosion. 3.
  - This brush cutter is designed for cutting brush,
  - undergrowth, grass and small irate attachments.

**Brush Cutter** 

v:122016

- The sharp blades on the cutting head rotate very fast and can cause injury or damage if the machine is not used in a careful and controlled way.
- 5. If you have not used a brush cutter before, familiarise yourself with how the machine works before you start on the main task.
- You must have at least the following items of personal protective equipment: 6. faceshield - impact resistant EN 166-B or BS2092 grade 1; ear muffs or plugs giving protection for levels up to 102 dB(A); safety helmet to EN397 or BS5240;
- safety bots to EN345 or BS1870/4972; gloves.
- 7. This machine must not be used by minors, o by anyone under the influence of
- drugs or alcohol.
- This machine is designed for operation by an able bodied adult. Anyone with 8 either temporary or permanent disability must seek expert advice before using it.

# Using the Brush Cutter

For guidance on managing

construction health risks go to www.hse.gov.uk/construction 

- 1. Wear your protective equipment including ear defenders, helmet, faceshield and safety boots.
- 2. Attach the brush cutter to your harness carefully.
- Make sure there is no-one in your area of work. 3.
- Always hold the brush cutter with both hands as well as using the harness. 4
- Make sure the cutting head is running at full speed before starting to cut into the 5. brush.
- 6. Keep the cutting head at or near ground level.
- 7. Beware of debris and dirt that may be thrown up by the blades.
- If the brush cutter starts to labour and slow down do not force it so hard. Do not 8. overload the engine.
- Stop the engine if someone approaches you. 9.
- 10. If you need to make adjustments to the blades or guard, stop the engine and wait until the blades have completely stopped. Wear your gloves to prevent cutting your hands while you make the adjustments.
- 11. Stop the engine before leaving the machine unattended.
- 12. If your equipment does not work properly do not attempt to repair it. Contact the hire company.

### Please keep this leaflet safely as it may be required for future reference



44 (0) 121 333 4109 ae.org.u e.org.uk

8. Put all tuel caps back on properly

If you spill any fuel on your clothes,

Dispose of fuel soaked cloth

Wipe any fuel off the machine.

refueling. Do not spill any fuel on

around it to prevent dirt falling into

Clean the filler cap and the area

It possible, move the machine away

Stop the engine and let it cool down.

prush cutter, you must know how to

the controls. Before you start the

cutting blades is in place and

9. Make sure that you understand all of

8. Make sure the guard around the

correct manner. Do not improvise.

attachments and fit them in the

Only fit the correct cutting

adjusting the blades or the guard.

6. Wear your gloves when fitting or

5. Use a funnel and clean petrol when

change them straight away.

yourseit or the machine.

from your work area.

sdjusted correctly.

-7

-9

·.

31

.S.

-2

caretully.

the fuel tank.

·биіхошя ом ·г

BEFUELLING

.ti qota

©Copyright Hire Association Europe April 2011

Any unauthorised reproduction – manually or electronically – is STRICTLY prohibited

oham Business Park

2450 Regents Court The Crescent olihull B37 7YE

part througe setting.

is running smoothly.

that it recoils correctly.

far or it may break.

sny obstruction.

PION COID

piace.

hire company.

cold start without using the choke or

use it. Return the brush cutter to the

while the machine is idling, do not

squeeze and release the throttle to

Guide the cord back into place so

quickly and strongly. Don't pull it too

engaged with the engine, then pull it

you can teel that the starter has

prevent movement, you will damage

Do not put your foot on the rube to

not move when you pull the starter.

with the cutting attachment clear of

The choke should be pulled put and

and move your fuel can to safe, cool

3. Hold the brush cutter firmly so it will

2. Lay the brush cutter on the ground

1. Set the engine controls correctly.

STARTING THE BRUSH CUTTER

the part throttle lock engaged.

4. Pull the starter grip out slowly until

8. If the cutting attachment rotates

Y. Turn the choke off when the engine

6. As soon as the engine has fired,

release the part throttle setting.

1. Follow the same procedures as for a





тон пэлW

<u>9</u>

