

GENERATOR SPECIFICATION			ENGINE SPECIFICATION	
Voltage	230/115		Engine	Kubota D722-E4B
Phase	1		Emissions certified	EU Stage V
Frequency	50Hz		Cylinders	3
Continuous Power (COP)	10.0 kVA / 8.0 kW		Aspiration	Naturally aspirated
Alternator	NSM C112 SB		Cooling	Water cooled
Fuel tank capacity	37 Litres		Displacement	719cc
Autonomy 100% load	10 Hours	3.7 L/h	Rpm	3000
Autonomy 75% load	13 Hours	2.8 L/h	Net Engine power	Net Intermittent
Autonomy 50% load	20 Hours	1.8 L/h		Continuous 10.3 kWm
Autonomy 25% load	41 Hours	0.9 L/h		
LWA	92			
dBA @ 7M	67			
dBA @ 4M	72			



DIMENSIONS (mm) & WEIGHT (KG)					POWER DEFINITION
Status	Length	Width	Height	Weight	Continuous Power (COP) : Applicable for supplying power to electrical load for unlimited hours in accordance with ISO 8528-1 under the agreed operating conditions with the maintenance intervals and procedures being carried out.
Skid dry	1285	655	900	301	
Skid wet	1285	655	900	332	

STANDARD FEATURES

- DSE 3110 control module - *See below for details.*
- Low oil pressure and high engine temperature shutdowns.
- Remote start facility.
- Battery isolator & emergency stop button for safety.
- Lifting eye.
- Oil drain facility .
- Fuel tank drain facility.

CONTROL PANEL

- DSE 3110 control module - *See below for details.*
- MCB overload protection.



- RCD earth leakage protection (230V).
- Voltage selector switch.
- Emergency stop button.
- 230V : 1 x 32A & 1 x 16A BS4343 sockets.
- 115V : 2 x 32A & 1 x 16A BS4343 sockets.
- Overload protection for each individual socket.
- Fuel gauge.
- Fuel pump prime button (easy bleed upon service).
- Remote start connections.

DEEP SEA ELECTRONICS 3110 START/STOP CONTROL MODULE

- The module will display warnings, shutdowns & engine status information on the back-lit LCD screen.
- Engine shutdowns include, high engine temperature & low oil pressure. low fuel level warning.

- Monitoring & protecting AC volts & frequency (Hz).
- Hours run counter.
- Battery voltage monitoring.
- 2-wire remote start function.



DSE

OPTIONS

- Industrial two wheel trolley kit with pneumatic wheels for easy transport & folding handles.



- ATS Panel (Automatic Transfer Switch).
- AVR (Automatic Voltage Regulator).
- Chalwyn valve/Spark arrestor.
- Customised socket arrangement on request.
- Mains battery charger.
- Auto start/stop programmable 7-day timer.

DIMENSIONS (mm) & WEIGHT (KG)

Status	Length	Width	Height	Weight
Trolley dry	1750	900	1080	357
Trolley wet	1750	900	1080	388