

Betore Starting Work...

## **WORK AREA**

- ·suppunders: It will ignite tumes from petrol or gas Do not use the laminate trimmer where there is a danger of explosion. 1
- safe and that no-one is near to you or could cause distraction. Warn Make sure that the area is clear and **'**Z
- others to keep away. Any work that is not part of a fixture 3
- °t In a vice. sponiq pe secniely clamped or held
- Joing to cut. gas or water pipes where you are If you are cutting into a fixture check there are no hidden electric cables,

## **SROTARAGO**

- The following items of protective minimum for the protective equipment (peed of the protective that should be worn whenever use the laminate triamer. Particular use the laminate triamer. Particular 1
- You must wear appropriate goggles when working with this machine. **'**Z obs or environments may require a nigher level of protection.
- °t
- When working with this machine." You will need to wear an appropriate dust mask (with a minimum of dust mask (with a minimum cutting materials that causes dust. This equipment is likely to cause noise levels up to 89 dB(A) wear hearing protection for this level as a minimum if you plan to operate the cause hands to tring enderate the machine for a long period. Make enquines regarding the there is no loose or flapping clothing the transke the to up weater the there is no loose or flapping clothing the transke to up weater the the transke to up weater the transke to the transke to up weater the transke to the transke transke to the tra 'G
- -9
- Anybody who is working near to you will also need to wear appropriate personal protective equipment.

- The laminate trimmer, when viewed from above, rotates clockwise. Pull the tool from left to right so that the rotating cutter bites into the work piece.
- **3YT TEB Iludilos** The Crescent Birmingham Business Park noo sinegen uce vesociation ⊨urope
- :lism3

effort has been made by HAE/EHA to ensure that the information given in this docum

0321 Safety Guidance

It is important to read this entire leaflet

**BEFORE using the Laminate Trimmer** 

be hazardous if used for a long time.

to cut anything containing asbestos.

before starting on the main task.

not used in a careful and controlled way.

RCD if using a 230 volt (mains) supply.

1. care.

3

4.

5.

6

7.

9

vibration.

required:

Gloves.

drugs or alcohol.

using the machine.

Electricity is hazardous and must always be used with

Machines that vibrate enough to make fingers tingle can

The laminate trimmer is designed to cut wood, laminates

and plastics using the appropriate cutters. Do not use it

Goggles - impact resistant EN166 - B or BA2092 grade 1;

Dust Mask - a minimum of EN149:2001 FFP3 protection; Ear Muffs or plugs giving protection for levels up to 85 dB(A);

Laminate Trimmer

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

The action of the laminate trimmer can cause injury or damage if the machine is

If you have not used a laminate trimmer before, practice on some scrap material

The following items of personal protective equipment are the minimum that is

This machine must not be used by minors or by anyone under the influence of

The laminate trimmer is designed for operation by an able-bodied adult. Anyone with either a temporary or permanent disability must seek expert advice before

is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability perceived to have arisen from the use of any such document/material. Only Acts of Parliament and Statutory Instruments

have the force of law and only the courts can authoritatively interpret the law.

**.** 

31

**.**2

\*

31

.s

- 1

20116

**CUTTERS** 

Plan work and think ahead to ensure safe working procedures are followed.

Investigate

- nae.org.u mail@hae.org.uk 44 (0) 121 333 4109 44 (0) 121 380 4600



















Ensure the cutter and collet are fitted

Eased. Ensure the correct type of cutter and collet recommended by the hite transmitter type of cutter and Ensure the correct type of cutter and East type of cutter and type of cutter

Do not use the laminate trimmer in the rain or where it might get wet. Check how the on / off switch operates before you switch the laminate trimmer on and know how to stop it.

Ensure the trimmer is held properly.

Check the machine, cutters and collets. If anything is found damaged, do not use the laminate trimmer - contact the hire company.

work piece

your equipment has a lock-off switch, switch it off or the plug, before changing the cutter.

Switch the laminate

**RAMINAT ATANIMAL** 

















# Using the Laminate Trimmer

For guidance on managing

construction health risks go to www.hse.gov.uk/construction v P S M Plant & Tool Hire Cen

- Wear your protective equipment including ear defenders and goggles. 1.
- 2. Always hold the trimmer properly when working. Keep hands clear of the cutter. If fingers start to tingle from vibration stop using the laminate trimmer, flex hands 3. and fingers to keep them warm and to encourage blood circulation. Investigate
- vibration. 4. To prevent damage to the cutter, check there are no nails, screws or metal
- embedded in your work piece.
- Allow the cutter to stop completely before withdrawing it from the work piece. 5.
- Keep the mains cable clear of the cutter and any sharp edges on the work. 6. If the cable appears to be cut or damaged in anyway, switch off the trimmer and 7. unplug at the mains before inspecting it. Do not use the machine. Contact the hire company. If an extension cable has been damaged do not use it again.
- Take care not to accidentally pull the plug from the socket. 8.
- Stop the machine and remove the plug before making any adjustments. 9.
- Switch off and store the laminate trimmer in a safe place before leaving it 10. unattended. If the laminate trimmer is not to be used for any length of time, it is safer to remove the cutter.
- 11. If your equipment does not work properly do not attempt to repair it. Contact the hire company
- 12. You may want to read this leaflet again. Please keep it until you finish work.

### Please keep this leaflet safely as it may be required for future reference



121 380 4600

e.org.uk www.hae.org.uk

44 (0) 121 333 4109

Ensure the extension safe.

·+

31

.S.

nəsn

Ensure the extension and called mine the extension cable out carefully vehicles might turn over it. Unroll truly or the extension cable will vehicles and places where it might vehicles and could catch fire.

The extension cable must be used between the transformer and

If an extension cable is required. cable is required. collow any special instructions, s usitably rated heavy duty 110v extension cable must be used, no longer than 50 metres (160 test). The extension cable must be test between the transformer and used between the transformer and

The machine will only operate on one voltage, it will be 110v or 230v. 110v machines will be take a veillow industrial plug fitted. 230v machines will have either a normal square pin plug fitted or instructions below for the machine to be used.

5

If using a portable transformer, plug the transformer, plug directly into the 230 volt socket. Do not volt socket. Do not extension cables extension cables

(легтом ыгле)

**SENIHOAM TLOV 011** 

ELECTRICAL SAFETY



©Copyright Hire Association Europe April 2011

Any unauthorised reproduction – manually or electronically – is STRICTLY prohibited

csple

Hire Association Euro 2450 Regents Court The C

and safe

the RCD.

.bagamab

cable

JO.

of qlad Iliw sidT Plug the machine into the 'RCD'.

directly into the 230v socket.

Use a residual current device ( ' R C D ')

. . C

·+

**'**Z

Ensure the extension cables are dry

liquids, sharp edges, doorways or windows where it might be trapped over it. Unroll fully or the cable could over it. Or of fully or the cable could

Lay the cable out carefully avoiding

metres (160 feet). Plug directly into

instructions, use only a suitably rated heavy duty cable no longer than 50

by the hire company. If the hire company of given any special

follow any special instructions given

RCD is working each time it is used. Reset the RCD according to the

Use the 'TEST' button to check the

machine

朝

t

<

protect against electric shock if the

pecomes

3. If an extension cable is required,

instructions supplied with it.

0101 b e p p u l q

(SQUARE PIN OR BLUE PLUG) **230 VOLT MACHINES** 

overneat and catch life.

Solihull B37 7YE