

P.S.M.Plant & Tool H



121 380 4600

e.org.uk www.hae.org.uk

44 (0) 121 333 4109

choke control to the coldstart position; if

It starting the machine from cold, adjust the

Check that the machine and machine controls are set correctly.

Not interview of the set on the ground or on a time level startice to bart, einber on the ground or on a sturdy hench; ensure that there is no debrits that could be sucked into and through the machine as it starts up.

It is good practice to start the machine in blower mode, this prevents the collection bag being inflated until the operator is ready,

Different machines may have slightly different starting procedures; use these guidelines in company or labels on the machine machine to find practice to start the machine in

Put all fuel caps back on properly, and move the fuel to a safe, cool place.

It any fuel is spilled on clothes they must be

Wipe any fuel off the machine. Dispose of fuel soaked cloth carefully.

A tunnel should be used when retuelling. Do not spill any fuel on people or the machine.

The filter cap and the area around it should be cleaned to prevent dirt falling into the fuel

It possible, the machine should be moved away from the work area.

The oil and petrol MUST be mixed in a separate container and NOT in the machines

instructions on how much oil to use, follow them. Otherwise use 1 measure of the 2 stroke oil to 25 measures of petrol (40 ml per (ilite).

Stop the engine and let it cool down.

Shake the fuel can to mix the petrol and oil.

If any fuel is spilled on the ground, wipe it up or cover it with soil.

**STARTING THE ENGINE** 

cuanged straight away.

°G

٠*t* 

3

.S

.11

.6

-2

**·**9

**.**G

.4

31

Before Starting Work...

Useful Reference Points • www.hae.org.uk/businessguard

rank.

rank.





## Using the Garden Vacuum/Blower

- Protective equipment must be worn including goggles, dust mask, ear defenders and gloves 1.
- Check that there is no waste material in the machine before the engine is started. 2
- Never out hands over the vacuum nozzle or the blower outlet while the machine is in operation 3
- Never point the machine at anyone, not even at a distance. 4.
- If it is necessary to clear a blockage, make an adjustment, or empty the collection bag, the machine 5. must be stopped and the engine and impeller fan allowed to come to a complete stop. For extra safety remove the spark plug lead, this will prevent the engine starting up unexpectedly.
- If any parts or tubes need to be removed to clear the blockage, note/remember how and where they 6. fit
- All the tubes and parts must be replaced before reconnecting the spark plug lead and starting the engine.

Please keep this leaflet safely as it may be required for future reference

©Copyright Hire Association Europe April 2011

Any unsuffortised reproduction – manually or electronically – is STHICILY prohibited

33

.5

-1

3

.S

1

.,

T

- 8. The engine must be stopped if anyone approaches whilst the operator is working.
- The engine must be stopped before leaving the machine unattended 9.

2450 Regents Court

lihull B37 7YE

future reference.

company.

GENERAL

оп ·7

BLOWER

Fusure

MUUDAV

·uonisod

obeu).

nacrine is running.

.buio

oniq otherw

The C

It way also be required for

Please keep this leaflet until the work has

If the equipment does not work properly, do not attempt to repair it. Contact the hire

security of the equipment; it should be stored

The operator is responsible for the safety and

it into piles, put it in containers and dispos-

not blow debris away from your

Do not point at, or touch anyone with the blower nozzle.

Do not attempt to empty the bag while the

etore

and then and then

herwise reduce the suction the bag is fully close

remove the spark plug lead to prevent accidential restart. Empty the bag completely and shake it vigorously to remove dust which plugw

Do not attempt to vacuum up liquids or w materials, the water will clog up the impelle and damage the machine.

The cord should be guided back into place so that it recoils correctly.

until the starter has engaged with the engine, It should be pulled too far, or it may break.

Aske sure that the machine is firmly held so that it will not move when the starter is pulled. The starter harder har experience with the starter harder har

If the machine has a fuel primer bulb, depress it 5 to 7 times to draw fuel into the carburettor

starting a machine that is still warm from use, the control can be set to the 'off'

and wait for it to stop completely, and

e the suction e

when using the machine as a blowe The vacuum collection bag is not needed

# Garden Vacuum/Blower

This safety instruction leaflet gives guidance on hand held machines only; most of these will incorporate a harness. Some machines will only operate as a garden vacuum, some are only garden blowers, but most machines can be used as a vacuum or blower.

### It is important to read all of this leaflet **BEFORE using the Garden Vacuum/Blower**

- Petrol is highly flammable. Take care not to cause a fire or exp This equipment is designed to blow leaves and other debris from gardens, paths and lawns into corners and other suitable areas, ready to be loaded into bags or containers for disposal, and to vacuum up outdoor areas that are lightly covered with garden debris into the collection bag ready for disposal. In use, this equipment can cause injury or damage if the machine is not used carefully and properly;
- (a)
- Do not point at, or touch, anyone with the suction nozzle or blower outlet;
- Removing the vacuum bag on some units may expose the fan/impeller; wait until the engine stops completely; (b)
- (c) Parts of this equipment get very hot; the operator must take care not to burn
- es or others If the machine is designed to be used with a harness, the harness must be used.
- erator must practice using the controls and operating the equipment before using it, if they have d it before. This must be done in a safe place until the operator is confident that they can e it safely. 5.
- The job must be planned to try to forsee any problems that may occur so that they can be safely 6.
- The following is a list of the minimum of Personal Protective Equipment (PPE) that must be worn:
- Ear muffs or plugs giving protection for levels up to 90dB (A); Impact resistant goggles: EN166 B or BS2092 grade 1;
- Gloves
- Strong sho Overalls or long sleeves and full trousers;
- A dust mask may also be required providing a minimum of EN149:2001 FFP3 protection;
- 8
- This machine must not be operated by minors, or by anyone under the influence of drugs or alcohol.is designed for use by an able bodied adult. Anyone with either a temp This garden blower is designed for operation by an able bodied adult. Anyone with either temporary or permanent disability must seek expert advice before using it. 9



ry effort has been made by HAE/EHA to ensure that the information given in this document and supporting mat is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability perceived to have arisen from the use of any such document/material. Only Acts of Parliament and Statutory Instruments have the force of law and only the courts can authoritatively interpret the law.



Anybody working nearby will also need to wear personal protective clothing... In case of an accident it is advisable to work who can offer assistance.

Long trousers must be worn and long sleeves to protect against ejected waste material and sharp thoms and insects.

Strong gloves should be worn for protection divers must not be worn; they may cause a mild-up of static electricity.

Impact resistant goggles must be worn when using the equipment as a blower (EN166 – B or BS2092 grade 1). If work is being carried out on a dusty surface an appropriate dust mask must be worn (with a minimum of EN1492,8001 FFP3 protection).

This equipment is likely to cause noise levels up to 90 dB(A) – appropriate ear mufts or plugs giving training protection for this level

bs or environments may require a higher vel of protection.

et of one of the second of personal protective promotes the minimum that should be added a second of other of the second of t

machine or collection bag if sucked in. Toylore starting the machine, removing hard injure someone if blown or would damage the machine or collection bag if sucked in.

Other people should be protected from noise and injury. Keep others, especially children put warning signs or barriers around the work area.

The area to be worked in should be clear and safe and there should be no-one nearby who could cause a distraction.

The reduce the risk of serious or tatal injury truncing theory of serious or tatal inducer be theory and the reset be used indoors. There must be proper ventilation when the equipment is being used in confined areas.

Oo not use this equipment next to petrol or De totrage areas or places where the will ignite an explosive attomacy and an oral price the petrol or totage of the mort and the petrol or totage of the petrol or totage of the petrol of the

umes from petrol, or gas cylinders.

The work area should be visually che

.9

·g

3

.s

·9

33

.s

nust be worn.

in son

**SHOTARAGO** 

еч⊥

area.

**MORK AREA** 

### The Crescent Birmingham Business Park vesociation ⊨urope

°t

.s

11

••

°t

3

**.**2

eq eqt t 31

**SSENRAH** 

send pottles.

hire company.

อนก 1

:lism3 :euoudeie







44 (0) 121 333 4109 44 (0) 121 380 4600

Use a fresh mixture of 2 stroke engine oil wi petrol. If the hire company have given spec

The shoulder harness should be put on and adjusted properly before carefully attaching the garden vacuum. Attach the equipment using only the correct clips and fastenings.

he harness attachment points are on the suum collection bag it usually means that harness only needs to be worn when wurming.

If the harness attachment points are on the machine, the harness subming adjusted. This applies to both vacuuming and blowing.

If the machine is designed to be used with a namese, if is because it is too heavy to be used without it.

The operator must understand all of the controls. Before the machine is started it must be understood how to stop it.

Do not use as a vacuum to collect water or nother liquics. Do not vacuum any mining that is we wet. Damp leaves or similar should be blown to a treach pile before vacuuming, this will remove access water. The operator must understand all of the

Prolonged vacuuming of fine dusts lik aswdust will clog up the collection bag and diminish suction. This will reduce th difficiency and overheat the machine.

The equipment should not be used as a general vacuum, or to pick up litter like cans

Check the engine, collection bag, hamess and all equipment. Anything found to be famaged should not be used. Contact the

MUUDAV/REWOLE NEGRAD

- - ю голокид.

  - - BEFUELLING