



Description: Aluminium Treble Extension Ladders



Professional Treble Extension Ladder is an industrial ladder fully compliant with the new EN131: Professional standard.

The ladders will safely support a maximum load of 150kg. Available in various sizes.

Approved to the latest EN131 Standard - For Professional Use.

SPECIFICATIONS

Code	EAN	Closed Height	Extended Height	Max Standing Height ¹	Width Closed	Width Open ²	Depth	Rungs	Weight
AEENT2.5	5011128996187	2.42m (7'11")	5.91m (19'4")	4.84m (15'10")	0.595m (1'11")	1.595m (5'3")	0.185m (0'7")	3 x 9	19.5kg
AEENT3.0	5011128996194	2.92m (9'7")	7.41m (24'3")	6.29m (20'7")	0.595m (1'11")	1.595m (5'3")	0.185m (0'7")	3 x 11	27.4kg
AEENT3.5	5011128996200	3.42m (11'2")	8.92m (29'3")	7.75m (25'5")	0.595m (1'11")	1.595m (5'3")	0.185m (0'7")	3 x 13	32.8kg
AEENT4.0	5011128996217	3.92m (12'10")	9.92m (32'6")	8.71m (28'7")	0.595m (1'11")	1.595m (5'3")	0.185m (0'7")	3 x 15	37.7kg

Maximum Standing Height: Ensure your ladder is long enough for the task at hand - when using a leaning ladder do not stand on the top three rungs to ensure maximum safety and stability. Note that ladders used for access should project at least 1m above the landing point and be tied in to provide a secure handhold.