## CM LODESTARELECTRIC CHAIN HOISTS 110v 32amp



## Electric chain hoist, model CM Lodestar

## Capacities: 1000kg

The Lodestar hoist is a tough and durable electric chain hoist, designed to keep working in the most arduous applications.

This hoist is recognised and proven within the hire industry as the number one hoist, where high duty, combined with long heights of lift are required.

From hook suspension in the rental industry to trolley mounted in a factory production line, the Lodestar has a proven reputation as the solution for industrial strength lifting.

Standard operating voltage: 110v 1ph 50Hz

Standard operating temperature -10° to +65°C

## Features and benefits include:

- Tough lightweight aluminium alloy covers totally enclose the mechanical and electrical components providing protection and efficient heat dissipation. The design enables easy access for installation and service.
- Adjustable upper and lower limit switches.
- 48v control, IP65 pendant as standard.
- Thermal overload protection as standard.
- FEM classification 2m (50% duty 30 minutes continuous use per hour).
- Motor classification H4.
- Excellent closed height dimensions.
- A lifetime lubricated gearbox contributes to exceptional service and maintenance characteristics.
- ✓ 3-phase single speed hoist motors are dual voltage.
- Load hook with axial bearing.
- Ideal for long heights of lifts.
- Large frame, single phase hoists are supplied with handles and 1mtr supply cable with Cee-Form plug.

TECHNICAL DATA						
Model	Operating voltage	Capacity (WLL) kg	Falls of load chain	Lifting speed(s) m/min	Load chain depth x pitch mm	Hoist motor kW
L	110v 1ph 50Hz	1000	1	4	7.9 x 21.7	0.75

