



Make: Youngman

Model: CatwalkS200

Description: Double 3m Fibreglass Extension Ladder



The 52781000 3.03m S200 Fibreglass Trade 2 Section Extension Ladder has non-conductive stiles making this ladder ideal for working around electricity and extends to a height of 5.06m. The exclusive ALFLO rung joint for Twist-Proof performance on the job. Suitable for trade use.

FEATURES

- **Non-conductive fibreglass stiles ideal for working around electricity**
 - **Alflo rung joints offer twist-proof performance**
- **Moulded foot brace provides enhanced bracing strength and protection against damage**
 - **Slip-resistant articulated feet for maximum ground contact**
 - **Heavy duty interior rope pulley for easy and safe operation**
 - **Semi-automatic locks**
 - **Slip-resistant D rungs for comfort and security**
 - **Manual thumb operated locking catch**
 - **Suitable for trade use**
 - **Safety certification: BS EN131**

SPECIFICATIONS

FEATURE	SIZE / DETAILS
Size	3.03m
Type	Trade 2 Section
Style	Double Section
Approx. Product Weight (kg)	17.2kg
Max. Open Extended Length (m)	5.06m
Safe Working Height (m)	5.6m
Number of Sections	2
Number of Treads	10
Material	Fibreglass
Colour of Ladder Rail	Yellow
Foot Design	Slip Resistant Articulated Feet
Foot Material	Steel / Rubber
Closed Length (m)	3.03m
Section x Rungs	2 x 10
Certifications	BS EN131
EAN	5013704111700
Rung Attachment	ALFLO
Rung Type	D-Rungs
Max. Load (kg)	150kg (23st 9lb)

*Safe working height based on 1.75m as the average reach height of a person.

**Load includes user, tools, materials, etc.