



# Low-level fibreglass platforms

The **Protec Podium** brings you all the advantages of a fibreglass access solution, non-conductive up to 100 kilovolts per foot, in the shape of a compact tower.

**Protec** Podium



- PAS250 compliant
- Non-conductive (100kv/ft)
- Chemical resistant
- Weather resistant
- Spark resistant
- Visible colour
- Non-slip platform deck
- Non-slip step treads
- Anti-slip feet
- Captive ladder
- Locking gate
- In-line castors



The podiums visible colour makes it stand out in a busy work environment, whilst a captive ladder, locking gate and in-line castors give it integral benefits. Working at height is made safer with the non-slip platform deck, step treads, and anti-slip feet. The podium is also chemical, weather and spark resistant.

Specification			
Platform height	950mm	1250mm	1500mm
Working height	2950mm	3250mm	3500mm
Overall height	2000mm	2300mm	2550mm
Working platform	607 x 625mm	607 x 625mm	607 x 625mm
Deployed footprint	1405 x 745mm	1600 x 1150mm	1700 x 1150mm
Stowed dimensions	2000 x 745 x 365mm	2250 x 745 x 485mm	2550 x 745 x 485mm
Safe working load	150kg	150kg	150kg
Weight	44kg	50kg	52kg



This data sheet is intended as a guide only and as such is not legally binding. Nor does it form part of any contract. All dimensions and weights are approximate.

