The TS 55 plunge-cut saw and the new guide rail

Data and Facts





Unique in its versatility!

- Non-tiring work thanks to particularly low weight.
- Fast-fix spindle stop for quick and easy saw blade changing.
- Virtually splinter-free cuts on both sides thanks to the splinterguard on the guide rail and the attachable splinterguard.



Description and application

Parallel stop/table widener for TS 55 Bilateral parallel stop, also usable as table

PA-TS 55, Order no. 491469

Cover/false joint stop for TS 55 Cover for enhanced dust extraction, eg when


sawing MDF, also usable as a false joint stop for sawing false joints

ABSA-TS 55, Order no. 491750

Splinterguard for TS 55

For splinter-free cuts, splinter-free on both sides when used with guide rail Qty. in pack: 5 x splinterguards, 1 x locking screw

SP-TS 55, Order no. 491473



Technical data	with electronics	without electronics
Power output	1200 W	1050 W
Saw blade speed	2000 – 5200 rpm	6500 rpm
Saw blade diameter	160 mm	160 mm
Inclined position	0° - 45°	0° - 45°
Cutting depth at 90°	0 - 55 mm	0 – 55 mm
Cutting depth at 45°	0 – 43 mm	0 – 43 mm
Connection for dust extraction, dia.	27/36 mm	27/36 mm
Weight	4.5 kg	4.5 kg
















Using the TS 55 to saw MDF: clean, quick and tested for use on Australian building sites.



The Expert in Guidance.

- Clean, splinter-free cuts thanks to the guide system with the
- Dead-straight results when sawing and routing with the guide rail.
- Convenient use of professional accessories thanks to the second

Version	Order no.
FS 800/2 Length: 800 mm	491499
FS 1080/2 Length: 1080 mm	491504
FS 1400/2 Length: 1400 mm	491498
FS 1900/2 Length: 1900 mm	491503
FS 2400/2 Length: 2400 mm	491502
FS 3000/2 Length: 3000 mm	491501
FS 5000/2 Length: 5000 mm	491500
Rails for rows of holes	
FS 1080/2-LR 32 Length: 1080 mm	491621
FS 2424/2-LR 32 Length: 2424 mm	491622



Using the TS 55 to saw timber floors:

System accessories



Return stop/Guide stop

FS-KS, Order no. 491588

Combi-bevel

is inserted into the 2nd groove on the guide rail and overlaps the base plate of the circular saw for TS 55, ATF 55, AP 55, AT 65, AP 65, AP 85

Description and application

for mounting in the 2nd groove on the guide

rail, makes precise angled cuts between 0°

FS-RSP, Order no. 491582

Sliding surface

Spare sliding surface for guide rail, 10 m roll

FS-GB 10M, Order no. 491741

Quick-action clamp

for clamping and positioning the Festool guide rails Scope of delivery: blade clamps, fixed clamps Qty. in pack: 1

FS-RAPID, Order no. 489790

Lever clampQuick and easy clamping Fitting width: 60 mm

FS-HZ 160, Order no. 491594

Polished steel version Fitting width: 120 mm, Qty. in pack: 2

FSZ 120, Order no. 489570

Fitting width: 300 mm, Qty. in pack: 2

FSZ 300, Order no. 489571

for connecting two guide rails for long workpieces, Qty. in pack: 1

FSV, Order no. 482107

prevents the suction hose and the cable

FS-AW, Order no. 489022

Splinterguard Spare splinterguard for guide rail

Length: 800 mm

FS-SP 800, Order no. 488468

Length: 1400 mm FS-SP 1400, Order no. 483164

Length: 3000 mm FS-SP 3000, Order no. 488467

Adhesive sole plate

Spare adhesive sole plate for guide rails,

FS-HU 10M, Order no. 485724