

GENERATOR SPECIFICATION

Voltage	230/115
Phase	1
Frequency	50Hz
Prime Power (PRP)	4.0kVA / 3.2kW
Alternator	NSM K100F
Alternator Type	Brushless - Smooth Waveform
Fuel tank capacity	13.0 Litres
Autonomy 75% load	13.0 Hours
LWA	96
dBA @ 7M	71

ENGINE SPECIFICATION

Engine	Lombardini 15LD 350S
Emissions certified	N/A
Cylinders	Single
Distribution	O.H.V.
Aspiration	Normally aspirated
Cooling	Air
Displacement	349 cm ³
Rpm	3000
Starting system	Key - Electric start
Fuel	Diesel



DIMENSIONS (mm)			WEIGHT (KG)
Length	Width	Height	
775	475	560	92



CONTROL BOX

- 1 x 16A & 1 x 32A 115V BS4343 sockets.
- 1 x 16A 230V BS4343 socket.
- Reset circuit breaker overload protection.

STANDARD FEATURES

- Key start.
- Low oil pressure & battery charge fail warning lamps.
- Long run fuel tank.
- Easy carry fold-away handles.
- Brushless smooth waveform alternator.

OPTIONS

- Single voltage.
- Trolley kit.

POWER DEFINITION

Prime Power (PRP) :

Applicable for supplying power to varying electrical load for unlimited hours in accordance ISO 8528-1.