

LONG STANDING VALUE

The Titan® barrier is made from the strongest virgin materials available. The new design has been adapted to include some additional benefits, such as added vertical bars for increased rigidity.



STREFORT GUARANTEE

We are so confident in the reliability of our barrier feet- should there be an occurrence of broken feet, we will supply replacements at **NO EXTRA COST!**

*Subject to terms of 'Surefoot'' guarantee.



TITAN® FEATURES



DIMENSIONS	Weight	13kg (with Surefoot™ feet) 14kg (with Anti-Trip feet)
	Height	1005mm
	Width	2000mm
STANDARDS	Fully Compliant	BSEN8442 (wind stability) BSEN12899-1 (reflective only) Chapter 8 (Traffic Signs Manual) TSRGD* SSWRW**
MATERIAL	Body	Polypropylene
	Feet	Recycled PVC

^{*} Traffic Signs and General Directions ** Safety at Street Works Act



REFLECTIVE PANEL

- Class R1 high intensity reflective.
- 20% more reflectivity than standard lower grade reflective material.
- Conforms to EN12899-1



V SURELOCK OR™

- Barrier connector clip.
- Compatible with other styles of JSP barriers and other brands.
- Can be connected on uneven ground i.e. kerbs and rough terrain.



ANTI-TRIP FEET

- Scalloped design to prevent accidents.
- Black recycled PVC feet as standard.
- Increased visibility yellow version also available.



▼ TRANSPORTATION & STORAGE

- Carry handle makes the barrier easy to carry and reposition.
- Clever locking design maximises stability when stacked for storage/ transporting correctly.
- 40 barriers per pallet.



▼ STABILITY BLOCS & POLES

- Can be attached to a Surefoot Bloc™ for extra weight and stability.
- SurePole™ is extendable and attachable between one barrier and another.
- SurePole™ can be fixed with tie wraps for extra security.



BESPOKE BRANDING

- One-piece mould can be made in any colour.
- Feet can also be coloured to suit.
- Company branding can be embossed on the rear of the barrier.
- MOQ JSP red & blue with black embossing 120.
- MOQ custom colours with black embossing- 520.
- Embossed area 20cm x 9cm.









